

MANUAL AIR VENT VALVE

Application

The manual discharge valve **te-sa Art. 157L** was designed and built to allow air to vent from radiator-type heaters or fan coils in a quick and safe way. Thanks to its construction features it is equipped with high exhaust flow even with low operating pressures. With brass body and high-strength resin handwheel, it can be subjected to high operating temperatures for long periods without experiencing loss of performance or leakage caused by early wear of components. The hydraulic seal of the valve is made directly from the maneuvering monobloc rod-handwheel, which allows the perfect closure of the drain even with the application of low torque clamping.

Equipped with self-sealing gasket on the thread, it is very practical during installation. Having an elongated body, it is ideal to facilitate the vent and drainage in die-cast heating bodies where the wings make it difficult to access the handwheel. The characteristics of this valve allow its general use in distribution plants, in all those cases where it is necessary to discharge air or to drain small residues from pipes or components.

The chrome coating of both the external and internal parts of the body combined with the synthetic rod, prevent the deposit of impurities and incrustations that could lead in time to loss of fluid or difficulty in maneuvering.



Assembly

The manual air vent valve Art. **157** is installed on heating bodies or parts of the plant simply by screwing, which must be sufficient to produce the deformation of the PTFE gasket placed at the base of the thread. In the case of assembly on female threaded components with abundant rounding off of the inlet, the self-sealing seal of the valve may not deform sufficiently, and consequently not ensure the hydraulic seal. In these cases it is recommended to add a sealant on the thread, such as PTFE tape or semi-blocking glue..


Nel caso di montaggio su radiatori si consiglia di mantenere l'ugello di scarico della valvola orientato frontalmente ed inclinato verso il basso di circa 45°. This, in addition to the longer length of the valve, allows an easy collection, with the help of small containers, of the first water in the outlet as a result of the air discharge.



Technical specifications

- Maximum operating pressure 10 bar
- Maximum operating temperature 90 °C
- Maximum glycol percentage 30%
- Body in brass alloy CW614N UNI-EN12164 chrome-plated
- Rod with maneuvering pawl in high resistance acetalic resin
- Male threading ISO228
- Self-sealing on the thread by means of a pre-assembled PTFE ring
- Self-cleaning seat of discharge with 3 mm diameter
- Opening locking device to prevent that the rod comes out

Dimensions



Art.	A	B	C	EX
157L-02	1/4"	Ø 17	32	Ch.13
157L-03	3/8"	Ø 17	32	Ch.17